KETS Enterprise VPN
Client Installation & Configuration Guide
(Mac OS X)

**March 25, 2005**

Purchasing

To purchase the Mac OS X client, navigate your web browser to **http://www.apani.com/vpnclients.html** and follow the links to pay for and download the software.

Installing

To install the software:
- Extract the file that was downloaded during the purchasing process.
- Open the **cvc_mac-3.1.1** folder that was extracted above and then open the **MacOS X** folder.
- Double-click the **Nleac.dmg** file to mount the disk image on the desktop.
- Open the **Netlock EAC** disk image icon on the desktop.
- Double-click the **Nleac.pkg** file to begin the installation process, as shown below:

- Follow the prompts in the Installer until the software has been completely installed.
- After installing, you will be prompted to restart your computer.

Configuring

To access the VPN client, open your web browser and enter **http://127.0.0.1:9161/** as the address. The first time you run the client, you will see the screen shown below:

Fill in the form as shown below:


Click the **Next** button to continue configuring the client.

Select **User Name and Password Authentication** as shown below:

Click the **Next** button and enter the **User ID** that KETS assigned to you, like the example shown below:

(NOTE: If you are configuring the VPN client on a machine from which more than one person will connect, check the **Prompt:** checkbox so the software will ask for both a username and password each time you run it.)

Click the **Finish** button to complete the configuration process.

Connecting

Once you have configured the VPN client, you will be taken to the Connection page whenever you navigate to **http://127.0.0.1:9161/**, as shown below:

To establish the connection, enter your password and then click the **Connect** button.

Once the connection has been established, you will see the page shown below:

Disconnecting

When you are ready to disconnect from the KETS network, simply return to **http://127.0.0.1:9161/** in your web browser and click the **Disconnect** button.